

Product Code

UTD-1295 Laboratory Oven 50 lt.
UTD-1300 Laboratory Oven 120 lt.
UTD-1305 Laboratory Oven 250 lt.
UTD-1310-C Laboratory Oven 500 lt.
UTD-1315-C Laboratory Oven 700 lt.

Models for 220-240V 50 Hz, 1 p	UTD-1295	UTD-1300	UTD-1305
Models for 110-120V 60 Hz, 1 p	UTD-1295-N	UTD-1300-N	UTD-1305-N
Models for 380 V, 50 Hz, 3ph	UTD-1310-C	UTD-1315-C	
Models for 220V, 60Hz, 3ph	UTD-1310-NC	UTD-1315-NC	

Standards

EN 932-5, 1097-5; ASTM C127, C136, D558, D559, D560, D698, D1557, D1559 BS 1377:1, 1924:11; UNE 103300

UTEST UTD Series Laboratory Ovens have been designed for drying asphalt, soil, rock, concrete, aggregate or similar materials.

50, 120, 250, 500 and 750 liter capacity models are available.

Temperature range is from ambient to 200°C.

The interior is manufactured from stainless steel and the exterior is robustly constructed from sheet steel finished in powder coated paint.

All models are fan circulated (forced convection), fitted with direct reading digital control unit and equipped with PID digital control system, isolated double wall construction, gasket single door and heating elements designed into air channels.



UTD-1300



UTD-1315

	Internal Dimension	External Dimension	Weight (approx.)	Adjustable Shelves
UTD-1295	360x350x410 mm	570x610x600 mm	50 kg	2 pcs.
UTD-1300	400x500x610 mm	660x750x770 mm	57 kg	2 pcs.
UTD-1305	570x600x800 mm	800x850x1020 mm	95 kg	3 pcs.
UTD-1310	580x790x1100 mm	800x920x1410 mm	127 kg	4 pcs.
UTD-1315	570x890x1400 mm	800x1000x1600 mm	185 kg	5 pcs.