

UTEST supplies ASTM and IP Thermometers listed below which are in accordance with the specifications of the American Society for Testing and Materials (ASTM), Institute of Petroleum (IP) and British Standards (BS).

While these thermometers were designed for use in specific tests many of them are used in other applications when precision thermometers are required.

CAUTION

Please check the laws in your country before ordering mercury thermometers. There may restriction on their sale and shipment for the thermometers contains mercury.



Product Code	IP Ref.	ASTM Ref.	Range (°C)	Graduation	Immersion	Dimensions	Weight
UTGT-2000	38C	-	23 to 27	0.1 °C	Total	30x30x300 mm	0.1 kg
UTGT-2005	76C	-	10 to 55	0.5 °C	93 mm	30x30x300 mm	0.1 kg
UTGT-2010	8C	-	0 to 44	0.2 °C	65 mm	30x30x300 mm	0.1 kg
UTGT-2015	42C	-	-38 to +30	0.5 °C	250 mm	30x30x300 mm	0.1 kg
UTGT-2020	5C	7C	-2 to 300	1 °C	Total	30x30x300 mm	0.1 kg
UTGT-2025	6C	8C	-2 to 400	1 °C	Total	30x30x300 mm	0.1 kg
UTGT-2030	15C	9C	-5 to 110	0.5 °C	57 mm	30x30x300 mm	0.1 kg
UTGT-2035	16C	10C	90 to 370	2 °C	57 mm	30x30x300 mm	0.1 kg
UTGT-2040	28C	11C	-6 to 400	2.0 °C	Total	30x30x300 mm	0.1 kg
UTGT-2045	47C	13C	155 to 170	0.5 °C	Total	30x30x300 mm	0.1 kg
UTGT-2050	60C	15C	-2 to 80	0.2 °C	Total	30x30x300 mm	0.1 kg
UTGT-2055	61C	16C	30 to 200	0.5 °C	Total	30x30x300 mm	0.1 kg
UTGT-2057	-	17C	19 to 27	0.1 °C	Total	30x30x300 mm	0.1 kg
UTGT-2065	20C	33C	-38 to 42	0.2 °C	50 mm	30x30x300 mm	0.1 kg
UTGT-2070	59C	35C	90 to 170	0.2 °C	50 mm	30x30x300 mm	0.1 kg
UTGT-2075	35C	47C	58.6 to 61.4	0.05 °C	Total	30x30x300 mm	0.1 kg
UTGT-2080	-	57C	-20 to 50	0.5 °C	Total	30x30x300 mm	0.1 kg
UTGT-2085	63C	63C	-8 to 32	0.1 °C	Total	30x30x300 mm	0.1 kg
UTGT-2090	93C	110C	133.6 to 136.4	0.05 °C	Total	30x30x300 mm	0.1 kg
UTGT-2095	89C	113C	-1 to 175	0.5 °C	Total	30x30x300 mm	0.1 kg