

## EN EN 12390-4 and EN 772-1 AUTOMATIC COMPRESSION TESTING MACHINES WITH WELDED WALLS FOR MASONRY UNITS, CUBES AND CYLINDERS

### Product Code

**UTC-5729.FPR** 2000 kN EN 12390-4 and EN 772-1 Automatic Compression Testing Machines for Masonry Units, Cubes and Cylinders

**UTC-5739.FPR** 3000 kN EN 12390-4 and EN 772-1 Automatic Compression Testing Machines for Masonry Units, Cubes and Cylinders

**UTC-0210** High Precision Pressure and Electronic

**UTC-4682** Pedestal for 1500 kN, 2000 kN and 3000 kN Compression Testing Frames with Welded Walls

Models for 220-240V 50-60 Hz, 1 ph.	UTC-5729.FP	UTC-5739.FPR
Models for 110-120V 60 Hz, 1 ph.	UTC-5729.FPR-N	UTC5739.FPR-N

### Standards

EN 12390-4, EN 772-1

UTC-5729.FPR and UTC-5739.FPR models Automatic Compression Testing Machines are manufactured for compression testing of masonry units, cubes and cylinders acc. to EN standards. These machines also meet the requirements of CE norms with respect to the health and safety of the operator.

The machines allow inexperienced operators to perform the test. Once the machine has been switched on and the specimen is positioned and centered by the help of fixtures or/and concentric centering lines of lower loading platen, the only required operations are;

- Setting test parameters, including pace rate (only required when the specimen type is changed).
- Pressing the START button on the control unit.
- The machine automatically starts the rapid approach, when the specimen touches the upper platen the rapid approach is ended and starts loading at the pace rate that selected by user and stops once the specimen fails.
- Automatically saves the test parameters and test results.

The Machines consist of a welded steel frame (see table) and UTC- 4830FPR automatic hydraulic power pack with U-Touch PRO Control Unit.

UTC-4682 Pedestal that is made of steel to facilitate the user's placement of specimens in the machines for compression test should be ordered separately.

### Safety Features

- Maximum pressure valves to avoid machine overloading
- Limit switch for piston stroke
- Emergency stop button
- Removable transparent front and rear safety doors
- Software controlled maximum load value



UTC-5729 with UTC-4682

### Main Features

- Pace Rate control between 1 kN to 25 kN
- Accuracy Class 1 starting from with the 5% of the machine capacity, (Special calibration option Class 1 starting from 1% of the full range with UTC-0210)
- Supplied with factory calibration certificate for force transfer stability and the self-alignment of the upper loading platen conforming to EN 12390-4
- Tests automatically with closed loop control
- The tests can be performed by controlling the machine either on U-Touch PRO control unit (UTC-4930.FPR) or on a computer with using free UTEST Software (USOFT-4830.FPR) which is provided free of charge with the machines.
- Load measurement with a pressure transducer
- Hydraulic pump with dual stage for rapid approach
- Welded steel walled frame a single acting piston
- Piston return at the end of test automatically



### U-Touch PRO Control Unit

U-Touch PRO Control Unit UTC-4930.FPR is designed to perform automatically compression, flexure and splitting tensile strength tests of construction materials such as concrete, cement mortar, masonry units/blocks by controlling the Utest automatic compression / flexure testing machines.

All the operations of U-Touch PRO are controlled from the front panel touch screen display.

U-Touch PRO Control Unit has easy to use menu options. It displays all menu option listings simultaneously, allowing the operator to access the required option in a seamless manner to activate the option or enter a numeric value to set the test parameters. Digital graphic display is able to draw real-time "Load vs. Time", or "Stress vs. Time" graphics.

PLEASE see the pages of "U-Touch PRO Control Unit for Automatic Compression/Flexure Testing Machines" for details of the properties.



### UTEST Software

UTEST software USOF-4830.FPR provides to perform automatically compression, flexure and splitting tensile strength tests of construction materials such as concrete, cement mortar, masonry units/blocks by controlling the Utest automatic compression / flexure testing machines. The advantages of performing tests on computer with using UTEST Software, such as reporting, graphical output, etc. can be seen in detail at the pages of UTEST Software for Automatic Compression / Flexure Testing Machines.

### Optional Additional Frame

For compression and especially flexural testing, additionally second testing frame should be ordered separately.

In this case, the machines provide load control of two separate testing frames with closed-loop P.I.D control with automatic test procedure by using selecting test channel And additional selector valve.

Models	UTC-5729.SLP	UTC-5739.SLP
Capacity	2000 kN	3000 kN
Frame Type	Welded Steel	Welded Steel
Bearing Platens Dimensions (D)	310x510x50mm	310x510x50mm
Upper Bearing Block, (With Spherically Seating Assembly ) Dimensions (C)	310x510x50mm	310x510x50mm
Surface Hardness of Bearing Blocks	55 HRC	55 HRC
Flatness Tolerance	0,03mm	0,03mm
Piston Diameter	250 mm	300 mm
Piston Stroke	50 mm	50 mm
Maximum Vertical Clearance Between Bearing Blocks (E)	350 mm	350 mm
Horizontal Clearance (B)	360 mm	415 mm
For Cubes (up to) Specimens Sizes	Ø160x320 mm	Ø160x320 mm
For Cylinder (up to) Specimens Sizes	300 mm (**)	300 mm (**)
For Masonary Units (up to) Specimens Siz	300x500 mm (**)	300x500 mm (**)
Power	550 W	550 W
Oil Capacity	20 L	20 L
Maximum Working Pressureor	410 Bar	410 Bar
Dimensions (wxlxh) (Axd*xF)	820x550x1145 mm	875x550x1205 mm
Weight	965 kg	1205 kg
Pedestal (Optional)	UTC-4682	UTC-4682

(d\*) Depth (\*\*) Limited by capacity of the frame

The machines for cubes and cylinders are supplied complete with;

- 100 mm, 50 mm, 2x30 mm height x Ø205 mm distance pieces
- Fixture for Centering Specimens, compatible with 310x510x50 mm lower loading platen for 100 mm and 150 mm cubes, Ø100 mm and Ø150 mm cylinders (UTC-4626E)
- Scissor Jack for Loading Platens/Bearing Blocks, (UTC-4629)
- Removable transparent front and rear safety doors

Appropriate Distance piece/s for the cylinder and cube specimens with the height of lower than 150 mm should be ordered separately.

