

Product Code

UTC-0398E Portable Slump Test Set, EN
UTC-0400E Slump Test Set, EN
UTC-0402E Slump Cone, EN
UTC-0404E Slump Base Plate
500x500x60 mm with Handle, EN
UTC-0406 Slump Cone Funnel, Galvanized Steel
UTC-0408 Tamping Rod Ø 16x600 mm
UTC-0410 Tamping Rod Ø10x300 mm
UTGH-1605 Round Scoop, Medium
UTGM-0380 Steel Ruler 300x1 mm

Standards

EN 12350-2

The Slump test method is used for the determination of the consistency and workability of fresh concrete.

UTC-0398E and UTC-0400E Slump Test Sets are supplied galvanized to prevent corrosion.

All parts of the Portable Slump Test Set (UTC-0398E) can be carried together easily.



The Slump Test Set are supplied complete with;

- Slump Cone Top Dia: 100 ±2 mm / Base Dia: 200 ±2 mm / Height: 300 ±2 mm / Thickness 1,5mm
- Slump Base Plate 500x500x60 mm with Handle (with UTC-0400E)
- Slump Base Plate with Handle and Clamps (with UTC-0398E)
- Slump Funnel, Galvanized Steel
- Tamping Rod Ø 16x600 mm
- Round Scoop, medium
- Steel Ruler 300x1 mm

Dimensions	550x560x310 mm (packed)
Weight (approx.)	6 kg