

Product Code

UTG-0130 Laboratory Mixer 10 L
 UTAS-0187 Heating Mantle for UTG-0130
 UTG-0131 Spare Bowl for UTG-0130
 UTG-0132 Spare Whisk for UTG-0130

Models for 220-240V 50-60 Hz, 1	UTGE-0130	UTGE-0130
ph. Models for 110-120V 60 Hz, 1	UTGE-0130-N	UTGE-0130-N

The UTG-0130 10 litre capacity Laboratory Mixer is designed for mixing of soil and asphalt samples to be used for mechanical tests such as compaction, indirect tensile, Marshall etc. The mixing head rotates at speeds of 10 to 240 r.p.m. and the whisk from 20 to 480 r.p.m. The user can adjust rotation speed between given values easily by using a control knob fitted to the front panel.

The bituminous mixture must be prepared at the prescribed

temperature according to the EN standard. For this reason the mixer can be equipped with thermostatically controlled heater.

The Heating Mantle (Isomantle heater) has a digital thermostatic controller and used for heating the bituminous mixtures in the UTG-0130 up to 150°C. The Isomantle heater is supplied complete with PT100 temperature sensor.

Heating Mantle should be ordered separately.

The Laboratory Mixer is supplied complete with;

- Bowl, 10 Lt Capacity Stainless Steel
- Mixing Whisk



UTG-0130



UTG-0131



UTG-0132

Product Code	UTG-0130	UTAS-0187
Dimensions	600x620x700	
Weight (approx.)	mm310x380x200mm	65 kg 6 kg
Power	550 W	600 W