

Strength Tests

PREPARATION of MORTAR PRISMS for COMPRESSION TESTS

Product Code

UTCM-0875E Manuel Mortar Mixer, EN UTCM-0875A Manuel Mortar Mixer, ASTM UTCM-0876 Spare Bowl, 5 L UTCM-0878E Spare Beater, EN UTCM-0878A Spare Beater, ASTM

Models for 220-240V 50-60	UTCM-0875E UTCM-0875E
Hz, 1 ph. Models for 110-120V	UTCM-0875E-N UTCM-0875E-N

Standards

EN 196-1, 196-3, 413-2, 459-2, 480-1, 1015-2, 12617-4; ASTM C187, C305, AASHTO T129, T131, T162

The UTCM-0875 Manual Mortar Mixer has a 5 liter (approx.) capacity, they have been designed to mix mortars and cement pastes primarily to the requirements of standards.

The mixing paddles revolve at a rate of 140 rpm. with a planetary motion of 62 rpm. in low speed. In high speed, the paddles

at the rate of 285 rpm. with a planetary motion of 125 rpm.

The user can choose the speeds easily by using the switch fitted to the machine. There is a sand filling apparatus on the mixers to pour sand easily. The bowl and beater are easily fitted and removed from mixer.

The Manual Mortar Mixers are supplied complete with; • Bowl, 5 L (approx.) • Beater

Dimensions	300x555x610
Weight (approx.)	mm 54 kg
Power	200 W







UTCM-0878

🛅 🖸 😭 🖌

UTCM-0876

www.globallab.com.tn

